

AIR 45 (2V) is an air-operated industrial vacuum that can solve dust problems in almost any light industry. The maintenance-free Venturi system makes it possible to use this model for continuous use.

Available with ATEX Z22 or Z1, 2, 21 & 22 certification



### Features

- ✓ Compact and portable
- ✓ 2-unit Venturi system (continuous use / maintenance-free)
- ✓ Low air consumption
- ✓ Removable collection tank
- ✓ Powder coated steel construction
- ✓ Integrated cleaning system
- ✓ Lightweight and versatile

### Filtration

Primary Filter	Star
Surface Area	22 ft <sup>2</sup> (2 m <sup>2</sup> )
Media Class (IEC 60335-2-69)	Anti-static Polyester - Class M
Cleaning System	Manual

### Optionals

- Certified HEPA Class H14 (99.995% @ 0.18 µm)
- PTFE Coated Filter (Class M)
- NOMEX Heat Resistant Filter
- Cyclone Filter Protector
- Earth Grounding
- ATEX Certified Version (Zone 22)
- ATEX Certified Version (Zones 1, 2, 21 & 22)
- Partial or Full Stainless Steel Frame
- More Power Sources Available By Request

### AIR 45 (2V)

Air Supply	CFM (L/min)	105.9 (3000)
Air Supply Pressure	PSI (bar)	87 (6)
Air Supply Hose	in (mm)	3/8 (10)
Max Airflow	CFM (m <sup>3</sup> /h)	176.6 (300)
Max Water Lift	inH <sub>2</sub> O (mmH <sub>2</sub> O)	164.6 (4180)
Capacity	gal (L)	12 (45)
Dimensions	in (WxLxH)	23 x 25 x 47
Weight	lbs (kg)	108 (49)
Noise Level (EN ISO 3744)	dB(A)	73
Suction Inlet	in (mm)	3 (80)