



DM 40 OIL is a compact single-phase vacuum for collecting and separating oil and chips. It helps reduce costs associated with subtractive manufacturing by allowing wasted materials to be recycled.

Features

- ✓ Compact, portable and constructed with powder coated steel
- ✓ 3 powerful bypass motors with independent cooling
- ✓ Integrated sieve basket
- ✓ Liquid shut-off valve
- ✓ Tangential inlet with cyclone filter protector
- ✓ Large liquid capacity
- ✓ Oil-proof wheels and gaskets
- ✓ Coated filter to protect motor from mist

Filtration

Primary Filter	Mist-Proof Bag
Surface Area	4.5 ft ² (0.4 m ²)
Media Class (IEC 60335-2-69)	Polyester - Class L
Secondary Filter	Polypropylene (300 µm)



Optionals

- Stainless Steel Sieve Grid
- Accessory Basket
- Partial or Full Stainless Steel Frame
- Engineering Accessories
- More Power Sources Available By Request

DM 40 OIL

Voltage	V - Hz	115 - 60 1~
Power	HP (kW)	3.0 (2.3)
Max Water Lift	inH ₂ O (mmH ₂ O)	80.9 (2055)
Max Airflow	CFM (m ³ /h)	282.5 (480)
Solids Capacity	gal (L)	11 (40)
Liquids Capacity	gal (L)	26 (100)
Dimensions	in (WxLxH)	26 x 26 x 49
Weight	lbs (kg)	143 (65)
Noise Level (EN ISO 3744)	dB(A)	76
Suction Inlet	in (mm)	3 (80)