

ZEFIRO 75 is an ultra compact three-phase vacuum system. Its vertical platform is ideal for both confined spaces and highly mobile applications.

Available with ATEX Z22 certification



Features

- ✓ Compact, mobile and constructed with powder coated steel
- ✓ Side channel blower (continuous use / no maintenance up to 30,000 hours)
- ✓ Pressure relief valve
- ✓ Large filter surface
- ✓ Removable collection tank
- ✓ Performance indicator light
- ✓ Nylon air exhaust diffuser
- ✓ Integrated cleaning system

Filtration

Primary Filter	Star
Surface Area	32 ft ² (3 m ²)
Media Class (IEC 60335-2-69)	Antistatic Polyester - Class M
Cleaning System	Manual
Air Load - ft/min (m/h)	8.2 (123)

Optionals

- Certified HEPA Class H14 (99.995% @ 0.18 µm)
- PTFE Coated Filter (Class M)
- NOMEX Heat Resistant Filter
- Cyclone Filter Protector
- Earth Grounding
- Partial or Full Stainless Steel Frame
- Sieve Grid and Discharge Valve
- ATEX Certified Version (Zone 22)
- More Power Sources Available By Request

ZEFIRO 75

Voltage	V - Hz	230/460 - 60 3~
Power	HP (kW)	4.6 (3.5)
Continuous Water Lift	inH2O (mmH2O)	70.9 (1800)
Max Water Lift	inH2O (mmH2O)	69.3 (1760)
Max Airflow	CFM (m ³ /h)	264.9 (450)
Electrical Protection	IP Class	55
Capacity	gal (L)	26 (100)
Dimensions	in (WxLxH)	31 x 26 x 67
Weight	lbs (kg)	209 (95)
Noise Level (EN ISO 3744)	dB(A)	75
Suction Inlet	in (mm)	3 (80)