



DG 300 HD EX1/3D & DG 300 HD EX1/2D is a heavy duty three-phase vacuum for large volumes of medium-heavy dust. It's suited for continuous use and recommended for facilities that desire more automation.

Features

- ✓ Compact, portable and constructed with powder coated steel
- ✓ Side channel blower (continuous use / no maintenance up to 30,000 hours)
- ✓ Tangential inlet with cyclone filter protector
- ✓ Fork lift intakes and ring bolt
- ✓ Pressure relief valve
- ✓ Extra large filter surface
- ✓ Performance indicator light
- ✓ Stainless steel canister and H14 Hepa filter included
- ✓ Automatic filter shaker cleaning system



Filtration

Primary Filter	Star
Surface Area	129 ft ² (12 m ²)
Media Class (IEC 60335-2-69)	Antistatic Polyester - Class M
Cleaning System	Automatic
Air Load - ft/min (m/h)	6 (110)

Optionals

- PTFE Coated Filter (Class M)
- NOMEX Heat Resistant Filter
- Remote Control
- Pneumatic Cleaning System
- Partial or Full Stainless Steel Frame
- Earth Grounding
- Lifting Bracket
- More Power Sources Available By Request

DG 300 HD EX1/3D & EX1/2D

Voltage	V - Hz	460 - 60 / 3~
Power	HP (kW)	28.6 (21.3)
Continuous Water Lift	inH2O (mmH2O)	96.5 (2450)
Max Airflow	CFM (m ³ /h)	780.5 (1326)
Electrical Protection	IP Class	65
Capacity	gal (L)	58 (220)
Dimensions	in (WxLxH)	37 x 71 x 87
Weight	lbs (kg)	1786 (810)
Noise Level (EN ISO 3744)	dB(A)	78
Suction Inlet	in (mm)	5 (120)